



WPE Series

1-Layer Stretch / Cling Film Blown Film Machine

Model Shown : WPE-45SE5
Winder type : E5

PE Stretch Film / Cling Film Whole Plant Equipment PE 延伸膜 / 保潔膜整廠設備



WPE Series

1-Layer Stretch / Cling Film Blown Film Machine



Model Shown : WPE-75ST6
Winder type : T6

WPE/M Series

2-Layer Stretch / Cling Film Blown Film Machine



Model Shown : WPE/M-65ST6
Winder type : T6



Chyi Yang Industrial Co., Ltd.
其陽工業股份有限公司



Chyi Yang Industrial Co., Ltd.

其陽工業股份有限公司

No. 11, Dinghu 3rd St., Guishan Township, Taoyuan Township,
Taiwan Tel : 886-3-3288686 Fax : 886-3-3283737

E-mail : cymw@cymw.com.tw <http://www.cymw.com.tw>

Model No.型號	WPE-45	WPE-55	WPE-65	WPE-75	WPE/M-65
Screw Diameter 螺桿直徑 (mm)	45 x 1 set	55 x 1 set	65 x 1 set	75 x 1 set	65 x 2 sets
Output 產量 (Kg/hr) ※	20-50	30-70	40-100	70-150	70-150
Max. Film Width 最大膜寬 (mm)	700	1000	1200	1600	1700
Drive Motor 馬達	1 set	1 set	1 set	1 set	2 sets
Die Diameter 模頭	1 set	1 set	1 set	1 set	1 set

- ※ Output depending on film width, thickness, die size, raw material feather etc.
產量依膜寬、膜厚、模頭尺寸、原料特性等不同而改變。
- ※ All photos & specifications are for reference, the machines outlooking & specifications are changed without advanced notice.
所有的機器圖片&規格僅供參考，機器外觀及規格若有更改，不另通知。
- ※ For more details specification, special requirements & quotation, please kindly contact us.
詳細的規格、特殊要求&報價單，請與我們聯絡。
- ※ Options : Air Shaft, Fully Automatic Winder , Chiller, Auto-Loader, Tubular Controller etc.
選購配備：氣壓軸、全自動捲取機、冷凍機、吸料機、自動充氣等。

Winder Type



Type : E5 (Back-to-back manual cut & change reel winder) 背對背手動捲取機



Type : H5 (Back-to-back auto. cut & manual change reel winder) 背對背自動切割，手動換捲捲取機



Type : T6 (Back-to-back auto. cut & auto. change reel winder, front cutter) 背對背全自動捲取機，前飛刀型式



Type : TE5 (Back-to-back auto. cut & auto. change reel winder, back cutter) 背對背全自動捲取機，後飛刀型式

PE Stretch Film / Cling Film Rewinder Machine PE 延伸膜 / 保潔膜覆捲機

RW-1 Series



RW-2 Series



RW-3 Series



RWA Series



Specification

Model No. 型號	RW-1	RW-2	RW-3	RWA
Raw Material 使用原料	PE cling / stretch film (PE 保潔膜 / 延伸膜)			
Rewinding Width 覆捲寬度 (mm)	300	200-550	500	300-530
Rewinding Length 覆捲長度 (M)	30-300M	30-1000M	30-1000M	50-1500M
Rewinding Speed 覆捲速度 (M/Min)	0-600	0-150	0-1000	0-1000
Feed & Cut System 入料及切割系統	Fully feed, cut, change reel 全自動入料、切割、換捲	Manual feed, cut, change reel 手動入料、切割、換捲	Fully feed, cut, change reel 全自動入料、切割、換捲	Fully feed, cut, change reel 全自動入料、切割、換捲

- ◆ Specifications are subject to change due to technological improvement without advanced notice. 因技術改善而變更規格不另通知。
- ◆ Rewinding speed depends on material property, film width, thickness etc. 覆捲速度依原料特性、膜寬、膜厚等不同而變化。